



K55 SERIES ISOLATED BONNET DIAPHRAGM VALVE MASTER CHART

* FILL IN PROPER DESIGNATIONS TO DETERMINE PRODUCT NUMBER: **K 5 5 - X 2 - 4 0 0 0**

BODY SIZE (std)
 0 = 1/2"
 1 = 1"
 4 = 1-1/2"

END CONNECTIONS (X std)
 X = None

BODY & CAP MATERIAL (2 std)
 2 = Noryl

VALVE OPTIONS (00 std)

00 = NO	04 = Spring Closed 60#	14 = LS, Spring Closed 60#
03 = Spring Closed 30#	05 = Spring Closed 100#	15 = LS, Spring Closed 100#
	10 = NO, LS	SX = Special Valve **

SEAL MATERIALS (1 std)

OPT.	OPERATING DIAPHRAGM	SEALING DISK	DYNAMIC SEALS	STATIC SEALS	KIT SERIES
1	Buna-N	EP	EP	EP	RAE
5	Buna-N	Fluoroelast.	Fluoroelast.	Fluoroelast.	RAV
6	Buna-N	Butyl	Butyl	Butyl	RAJ

INTERNAL PARTS (4 std)
 4 = Noryl/PVC (140°F (60°C) Valve Rating)

DRILL & TAP BOSSES (0 std)
 0 = None

SOLENOID OPTIONS (0 std)
 0 = None

SOLENOID FEATURES (0 std)
 0 = None

* To create a valve number replace each "_" with the proper number or letter for the feature you desire.
 For example, a Normally Open 2" Plastic Valve Model K5524 with a Spring Assist Closed Option is designated as a K554-X202-14000.

** A special valve will have a custom drawing number (_____) and the item number format is (K55?-X2SX-_____) where the last 5 numbers (Far Right) are the last five digits of the drawing number.

REV.	ECO NO.	DESCRIPTION	BY/DATE
E	100997	Removed -02 & -12 valve options	TJM 8-Aug-12

16605 West Victor Rd. New Berlin, WI 53151
 P: 262-326-0100 | www.aq-matic.com | techsupport@aq-matic.com

© 2016 AQ Matic Valve and Controls Company, Inc. All rights reserved.

All AQ Matic trademarks and logos are owned by AQ Matic or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, AQ Matic reserves the right to change specifications without prior notice. AQ Matic is an equal opportunity employer.