



## V46 SERIES DIAPHRAGM VALVE MASTER CHART

\* FILL IN PROPER DESIGNATIONS TO DETERMINE PRODUCT NUMBER: V 4 6 - 2 - 3 0 0 0

**PIPE SIZE**  
 C = 1" (25mm)  
 E = 1-1/2" (40mm)  
 F = 2" (50mm)

**BODY SIZE** (Reference only)  
 1 = 1"  
 4 = 1-1/2"  
 5 = 2"

**END CONNECTIONS**  
 0 = Female N.P.T.                      3 = Flanged / Female N.P.T. Boss Taps

**BODY & CAP MATERIAL**  
 2 = 316 Stainless Steel (Cast CF8M)

**VALVE OPTIONS** (00 = Standard)

00 = NO	11 = NO, LS, SAO
01 = NO, SAO	30 = NC
02 = NO, SAC	32 = NC, SAC
10 = NO, LS	40 = NC, LS

**SEAL MATERIALS** (0 = Standard) (Option 5 not valid for NC valves)

OPT.	OPERATING DIAPHRAGM	SEALING DISK	DYNAMIC SEAL	STATIC SEALS
0	Buna-N	Buna-N	Buna-N	Buna-N
1	Buna-N	EPDM	EPDM	EPDM
2	FKM	FKM	FKM	FKM
4	FKM	EP	EP	EP
5	Buna-N	FKM	FKM	FKM
6	Buna-N	FDA Buna-N	FDA Buna-N	FDA Buna-N

**INTERNAL PARTS**  
 3 = 316 Stainless Steel

\* To create a valve number replace each " \_ " with the proper number or letter for the feature you desire. For example, a 1" NPT Stainless Steel Valve Model V461 with Normally Closed and Spring Assist Closed Options is designated as a V46C-0232-03000.

REV.	ECO NO.	DESCRIPTION	BY/DATE	
C	21190	Reviewed for AQ Matic ECN release	JJJ	17-Nov-09
D	103533	REM'D:FEMALE BSPT (TAPERED) THD OPTION	TJM	20-Jun-14

16605 West Victor Rd. New Berlin, WI 53151  
 P: 262-326-0100 | www.aq-matic.com | techsupport@aq-matic.com

© 2016 AQ Matic Valve and Controls Company, Inc. All rights reserved.

All AQ Matic trademarks and logos are owned by AQ Matic or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, AQ Matic reserves the right to change specifications without prior notice. AQ Matic is an equal opportunity employer.